AMENDMENT TO THE CLAIMS

Kindly amend the claims as follows:

- 1. (Currently Amended) Vulcanizable rubber mixes comprising:
- a) rubbers,
- b) O,O-bis-(alkyl)dithiophosphoric acid polysulfides corresponding to the formula

$$\left((RO)_{2} - P - \right)_{2} S_{x}$$

wherein

- x represents 2, 3, 4 or 5 and
- R represents a C₈-C₁₂-alkyl or –cycloalkyl radical

and

c) primary and/or secondary amines corresponding to the formula

$$Y - N < R_1 \atop R_2$$

wherein

- Y represents hydrogen or a mercaptobenzothiazole radical,
- R₁ represents hydrogen, C₁-C₆-alkyl, C₅ or C₆-cycloalkyl C₇-C₁₂- aralkyl and
- R_2 has the same meaning of R_1 , with the proviso that R_1 and R_2 do not simultaneously represent hydrogen,

At

wherein the components b) and c) are in a molar ratio from (0.5 to 1.5): 1 and are present in a total amount of from 1 to 10 parts by wt. per 100 parts by wt. of rubbers in the rubber mixes, and

d) 0.5 to 3.0 wt.-% sulfur, based on the rubber.

- 2. (Currently Amended) Rubber molded products comprising vulcanizable rubber mixes comprising:
- a) rubbers,
- b) O,O-bis-(alkyl)dithiophosphoric acid polysulfides corresponding to the formula

$$\left((RO)_{2} \xrightarrow{\stackrel{S}{|I|}} S_{x} \right)$$

wherein

x represents 2, 3, 4 or 5 and

R represents a C₈-C₁₂-alkyl or -cycloalkyl radical

and

c) primary and/or secondary amines corresponding to the formula



wherein

Y represents hydrogen or a mercaptobenzothiazole radical,

R₁ represents hydrogen, C₁-C₆-alkyl, C₅ or C₆-cycloalkyl C₇-C₁₂- aralkyl and

 R_2 has the same meaning of R_1 , with the proviso that R_1 and R_2 do not simultaneously represent hydrogen,

OH

wherein the components b) and c) are in a molar ratio from (0.5 to 1.5): 1 and are present in a total amount of from 1 to 10 parts by wt. per 100 parts by wt. of rubbers in the rubber mixes, and

d) 0.5 to 3.0 wt.-% sulfur, based on the rubber.


(Original) A rubber molded product according to Claim 2, wherein said rubber molded product is selected from the group consisting of tires, hoses, damping components, seals and profiles.

(New Claim) A process for preparing vulcanizable rubber mixes according to claim 1 which may be vulcanized with a high crosslink density and a high proportion of short sulfur bridges, which process comprises mixing the rubbers a) with the

components b), c) and d).

(New Claim) A process for increasing the crosslink density and the proportion of monosulfide sulfur bridges in the vulcanization of a rubber mix comprising a) rubbers and d) 0.5 to 3.0 wt.-% sulfur, based on the rubber, by using a combination of

b) O,O-bis-(alkyl)dithiophosphoric acid polysulfides corresponding to the formula



wherein

represents 2, 3, 4 or 5 and

R represents a C₈-C₁₂-alkyl or -cycloalkyl radical

and

Mo-5874

c) primary and/or secondary amines corresponding to the formula

$$Y - N < R_1$$


wherein

Y represents hydrogen or a mercaptobenzothiazole radical,


R₁ represents hydrogen, C₁-C₆-alkyl, C₅ or C₆-cycloalkyl C₇-C₁₂- aralkyl and

 R_2 has the same meaning of R_1 ,

with the proviso that R1 and R2 do not simultaneously represent hydrogen, wherein the components b) and c) are in a molar ratio from (0.5 to 1.5): 1 and are present in a total amount of from 1 to 10 parts by wt. per 100 parts by wt. of rubbers in the rubber mixes.



7. (New Claim) <u>Vulcanizable rubber mixes according to claim 1, wherein</u> component b) is a compound of the formula



wherein x is 2 - 5.